

Concrete mixer bucket 150 litres

Capacity 150 litres
Item number:SI150

Technical data:

Type	Unit	SI150
Recommended capacity	liter	150
Max capacity	liter	180
Weight (empty)	kilogram	240
Weight (full)	kilogram	ca. 600
Recommended/max. oil flow	liter/minute	40/75
Continuous/max. pressure	bar	130/180
Transmission	gearbox	
Draininghose	hydraulic	

Equipment of our concrete mixer buckets

- 150 litres, max. capacity 180 litres
- Weight: approx. 240 kg – Weight with concrete: approx. 600 kg
- Danfoss hydraulic motor OMR 160 with gearbox
- Inner lining of the bucket in Steel Fe510 (S355) - thickness: 6 mm
- Auger from HARDOX 500 – thickness: 12 mm
- Safety grid with prongs for opening the cement bags
- 6/2 valve for switching between mixing and hydraulic draining device
- Draininghose, length: 2 m
- 2 pieces hydraulice hose and socket as well as cable set

Optionally available:

- Suitable holder for carrier device
- Inner lining of the bucket in HARDOX 450 - thickness: 4 mm
- Gas spring for protective lattice incl. shut-off valve engine (lt. CE NORM)
- Diaphragm accumulator (pressure compensation for various carrier devices)

