

Concrete mixer bucket 400 litres

Capacity 400 litres
Item number:SI400

Technical data:

Type	Unit	SI400
Recommended capacity	liter	400
Max capacity	liter	470
Weight (empty)	kilogram	560
Weight (full)	kilogram	ca. 1.500
Recommended/max. oil flow	liter/minute	65/90
Continuous/max. pressure	bar	160/190
Transmission	chain	
Draininghose	hydraulic	

Equipment of our concrete mixer buckets

- 400 litres, max. capacity 470 litres
- Weight: approx. 560 kg – Weight with concrete: approx. 1.500 kg
- Danfoss hydraulic motor OMS 400 with gearbox
- Inner lining of the bucket in Steel Fe510 (S355) - thickness: 8 mm
- Auger from HARDOX 500 – thickness: 15 mm
- Safety grid with prongs for opening the cement bags
- 6/2 valve for switching between mixing and hydraulic draining device
- Draininghose, length: 2 m
- 2 pieces hydraulic hose and socket as well as cable set

Optionally available:

- Suitable holder for carrier device
- Inner lining of the bucket in HARDOX 450 - thickness: 4 mm
- Gas spring for protective lattice incl. shut-off valve engine (lt. CE NORM)
- Diaphragm accumulator (pressure compensation for various carrier devices)

