

## Concrete mixer bucket 750 litres

Capacity 750 litres  
Item number:SI750

### Technical data:

| Type                      | Unit         | SI750     |
|---------------------------|--------------|-----------|
| Recommended capacity      | liter        | 750       |
| Max capacity              | liter        | 800       |
| Weight (empty)            | kilogram     | 920       |
| Weight (full)             | kilogram     | ca. 2.700 |
| Recommended/max. oil flow | liter/minute | 125/240   |
| Continuous/max. pressure  | bar          | 180/200   |
| Transmission              | chain        |           |
| Draininghose              | hydraulic    |           |

### Equipment of our concrete mixer buckets

- 750 litres, max. capacity 800 litres
- Weight: approx. 920 kg – Weight with concrete: approx. 2700 kg
- Danfoss hydraulic motor OMV 630 with chain drive
- Inner lining of the bucket in Steel Fe510 (S355) - thickness: 10 mm
- Auger from HARDOX 500 – thickness: 15 mm
- Safety grid with prongs for opening the cement bags
- 6/2 valve for switching between mixing and hydraulic draining device
- Draininghose, length: 2 m
- 2 pieces hydraulic hose and socket as well as cable set

### Optionally available:

- Suitable holder for carrier device
- Inner lining of the bucket in HARDOX 450 - thickness: 5 mm
- Gas spring for protective lattice incl. shut-off valve engine (lt. CE NORM)
- Diaphragm accumulator (pressure compensation for various carrier devices)

